

elson PRESS BALL VALVE (WATER)



elson PRESS WATER BALL VALVE LF DR BRS L/H

Code: 73660 15mm x Rp1/2
Code: 73662 20mm x Rp3/4



elson PRESS WATER BALL VALVE LF DR BRS T/H L/NUT

Code: 73672 15mm x G3/4



elson PRESS WATER BALL VALVE LF DR BRS L/H

Code: 73680 15mm
Code: 73686 32mm

Code: 73682 20mm
Code: 73688 40mm

Code: 73684 25mm
Code: 73690 50mm

FEATURES

- Manufactured by elson, certified to ISO 9001
- WaterMark Certificate No. WMKA 21922, Conforms with 5830.1
- Ball valve body: Allowable operating pressure (AOP): 2500kPa
- Press end connection: Allowable operating pressure (AOP): 1600kPa to AS3688
- Every valve is pressure tested by elson prior to release
- Working temperature from -20°C to 95°C
- 1/4 Turn full-bore for optimum water flow
- Lead Free DR Brass
- elson PRESS to suit only Type A and / or Type B copper tube complying with AS1432



Elson Australasia Pty Ltd

ABN 45 059 613 991

38 Eddie Road, Minchinbury NSW 2770

Tel: (02)9625 7899

Fax: (02)9625 7855

Email: sales@elson.net.au

elson PRESS BALL VALVE (GAS)



elson PRESS GAS BALL VALVE LF DR BRS L/H

Code: 73560 15mm x Rp1/2
Code: 73562 20mm x Rp3/4



elson PRESS GAS BALL VALVE LF DR BRS T/H L/NUT

Code: 73572 15mm x G3/4



elson PRESS GAS BALL VALVE LF DR BRS L/H

Code: 73580 15mm
Code: 73586 32mm

Code: 73582 20mm
Code: 73588 40mm

Code: 73584 25mm
Code: 73590 50mm

FEATURES

- Manufactured by elson, certified to ISO 9001
- AGA approved NO.8350, Conforms with AS4617
- Ball valve body: Allowable operating pressure (AOP): 1050kPa
- Press end connection: Allowable operating pressure (AOP): 500kPa to AS3688
- Every valve is pressure tested by elson prior to release
- Working temperature from -20°C to 95°C
- 1/4 Turn full-bore for optimum flow
- Lead Free DR Brass



AGA 8350
AS 4617

Elson Australasia Pty Ltd

ABN 45 059 613 991

Version 2.0 June 2021

38 Eddie Road, Minchinbury NSW 2770

Tel: (02)9625 7899

Fax: (02)9625 7855

Email: sales@elson.net.au