

**elson LF PRESS BALL VALVE
(WATER)**



elson LF PRESS WATER BALL VALVE LF DR BRASS L/H

Code: LF73660 15mm x Rp1/2
Code: LF73662 20mm x Rp3/4

elson LF PRESS WATER BALL VALVE LF DR BRASS T/H L/NUT

Code: LF73672 15mm x G3/4



elson LF PRESS WATER BALL VALVE LF DR BRASS L/H

Code: LF73680 15mm
Code: LF73686 32mm

Code: LF73682 20mm
Code: LF73688 40mm

Code: LF73684 25mm
Code: LF73690 50mm

FEATURES

- WaterMark Certificate No. WMKA 21922, Complies with 5830.1
- Ball valve body: Allowable operating pressure (AOP): 2500kPa
- Press end connection: Allowable operating pressure (AOP): 1600kPa
- Every valve is pressure tested by elson prior to release
- Working temperature from -20°C to 95°C
- 1/4 Turn full-bore for optimum water flow
- **LEAD FREE*** DR Brass
- elson PRESS to suit only Type A and / or Type B copper tube complying with AS1432
- Manufactured by elson, certified to ISO 9001

* Elson Lead Free copper alloy products are 99.9% Lead Free and contain less than 0.1% Lead by weight.



**elson LF PRESS BALL VALVE
(GAS)**



elson LF PRESS GAS BALL VALVE LF DR BRASS L/H

Code: LF73560 15mm x Rp1/2
Code: LF73562 20mm x Rp3/4

elson LF PRESS GAS BALL VALVE LF DR BRASS T/H L/NUT

Code: LF73572 15mm x G3/4



elson LF PRESS GAS BALL VALVE LF DR BRASS L/H

Code: LF73580 15mm	Code: LF73582 20mm	Code: LF73584 25mm
Code: LF73586 32mm	Code: LF73588 40mm	Code: LF73590 50mm

FEATURES

- AGA approved NO.8350, Conforms with AS4617
- Ball valve body: Allowable operating pressure (AOP): 1050kPa
- Press end connection: Allowable operating pressure (AOP): 500kPa
- Every valve is pressure tested by elson prior to release
- Working temperature from -20°C to 95°C
- 1/4 Turn full-bore for optimum flow
- **LEAD FREE*** DR Brass
- Manufactured by elson, certified to ISO 9001

* Elson Lead Free copper alloy products are 99.9% Lead Free and contain less than 0.1% Lead by weight.

